

CSX Transportation

Intermodal Cranes



13 RMG manufactured by Kuenz for a new generation of US intermodal terminals

Kuenz's RMG ensure efficiency in CSX Intermodal Terminals.

Wilby Whitt, President CSX Intermodal Terminals

«When we built our new state-of-the-art Northwest Ohio Intermodal Terminal, we required the most technologically and environmentally advanced equipment in the world. We worked with Kuenz on this daunting challenge and had tremendous results. The cranes provided by Kuenz helped us lead the industry by reducing emissions and improving the efficiency of operations. Our successful endeavor has led us to explore more opportunities together. We look forward to working with Kuenz once again to continue our pursuit of environmentally-friendly freight transportation solutions.»



The first crane installations for Kuenz in North America at the Northwest Ohio Terminal.

CSX is one of the leading transportation companies in the U.S. providing rail-based services as well as transport of intermodal containers and trailers. The company serves major markets in the U.S. and operates 50 terminals across the eastern United States.

First RMG for Kuenz in North America

For CSX's newly designed Terminal in Northwest Ohio (NWOH), Kuenz supplied five wide span ultra-efficient electric RMG. This new terminal is a a cornerstone between East Coast seaports and Midwestern markets by creating a double stack freight rail corridor. The 500-acre area has been designed as a hub terminal to handle much more volume then most intermodal terminals. The new concept allows for the handling of up to 35 trains per day and 1.2-1.5 million TEU annually. The delivery of the five wide span RMG in 2010 was the first reference installation for Kuenz in North America. Another two identical wide span RMG were added in 2015.

Kuenz performance leads to subsequent orders

Satisfied by the NWOH installations, CSX ordered Kuenz RMG also for hub terminals in Florida and Ohio. Three RMG, designed as double-girder bridges, are proper operating at the Terminal Winter Haven in Florida.

Another three Kuenz Intermodal cranes are custom-built for a smooth travelling on curved rail tracks at CSX's Terminal in Columbus, Ohio.

ntermodal Cranes in Columbus, Ohio are travelling on a curved rail track

Kuenz Technology - Moving through the curve

The layout of the Columbus terminal features curved rail tracks, which required a sophisticated design. The main bogie, the intermediate bogies as well as each single wheel bogie can be rotated horizontally. Each wheel bogie is equipped with four horizontal rollers to guide the bogies and distribute the horizontal loads equally. The four horizontal rollers on each wheel bogie guarantee less wear on the wheels, rollers and the crane runway. The crane posts (fixed post and hinged post) are electronically synchronized. These design features allow the crane to move safe and smoothly through the curve.



Kuenz RMG in Winter Haven, Florida



Technical Data - CSX Cranes.

Terminal North Baltimore, Ohio: 7 RMG

| 2015 |
|---------------------|
| 46 t |
| 45.7 m |
| 16.6 m |
| 20.9 m |
| 15.4 m |
| |
| 0 – 25 m/min |
| 0 – 50 m/min |
| 0 – 120 m/min |
| 0 – 150 m/min |
| 0 – 1.5 rpm |
| |
| 275 kW / 100%ED |
| 24 x 19 kW / 100%ED |
| 4 x 32 kW / 100%ED |
| 2 x 7 kW / 100%ED |
| |

Terminal Winter Haven, Florida: 3 RMG

| Year of construction: 2013 | |
|----------------------------|---------------------|
| Capacity main hoist | 41 t |
| Track width | 45.7 m |
| Cantilever fixed column | 16.9 m |
| Cantilever hinged column | 13.2 m |
| Lifting height | 15.2 m |
| Working speeds: | |
| Hoist rated load | 0 – 25 m/min |
| Hoist partial load | 0 – 50 m/min |
| Gantry drive | 0 – 120 m/min |
| Trolley drive | 0 – 150 m/min |
| Slewing | 0 – 1.5 rpm |
| Power: | |
| Main hoist | 275 kW / 100%ED |
| Gantry drive | 24 x 19 kW / 100%ED |
| Trolley drive | 4 x 32 kW / 100%ED |
| Slewing | 2 x 7 kW / 100%ED |

Terminal Columbus, Ohio: 3 RMG

| Year of construction: 2012 | |
|----------------------------|---------------------|
| Capacity main hoist | 41 t |
| Track width | 34.7 m |
| Travelling on curved rail | Radius: 582 m |
| Cantilever hinged column | 12.5 m |
| Lifting height | 12.3 m |
| Working speeds: | |
| Hoist rated load | 0 – 25 m/min |
| Hoist partial load | 0 – 50 m/min |
| Gantry drive | 0 - 120 m/min |
| Trolley drive | 0 - 150 m/min |
| Slewing | 0 – 1.5 rpm |
| Power: | |
| Main hoist | 275 kW / 100%ED |
| Gantry drive | 20 x 19 kW / 100%ED |
| Trolley drive | 4 x 32 kW / 100%ED |
| Slewing | 2 x 7 kW / 100%ED |

North Baltimore, Ohio Columbus, Ohio

Winter Haven, Florida

Further information: www.kuenz.com

Künz GmbH 6971 Hard Österreich / Austria sales@kuenz.com www.kuenz.com